


## 1-Line, Uni-directional, Transient Voltage Suppressor



### Features


- Stand-off voltage: 24V Max
- Transient protection for each line according to  
IEC61000-4-2(ESD):  $\pm 30\text{kV}$  (contact)  
IEC61000-4-5(surge): 200A (8/20 $\mu\text{s}$ )
- Low leakage current
- Low clamping voltage
- Low clamping voltage:
- RoHS Compliant

### Applications

- Power Management
- Industrial Application
- Power Supply Protection


### Mechanical Data

- Package: DFN2020-3L
- Case Material: "Green" Molding Compound
- Marking Information: See Below



6161/24 = Device Marking Code  
XX = Date code

### Definitions of electrical characteristics





# PESD24VP4A1

## ■Maximum Ratings

PARAMETER	SYMBOL	LIMITS	UNIT
Peak pulse power ( $t_p = 8/20\mu s$ )	$P_{pk}$	6400	W
Peak pulse current ( $t_p = 8/20\mu s$ )	$I_{PP}$	200	A
ESD according to IEC61000-4-2 air discharge	$V_{ESD}$	$\pm 30$	KV
ESD according to IEC61000-4-2 contact discharge		$\pm 30$	
Junction temperature	$T_J$	-55~125	$^{\circ}C$
Storage temperature	$T_{STG}$	-55~150	$^{\circ}C$

## ■Electrical Characteristics ( $T_a=25^{\circ}C$ Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	$V_{RWM}$	V				24
Reverse breakdown voltage	$V_{BR}$	V	$I_{BR} = 1mA$	25		
Reverse leakage current	$I_R$	$\mu A$	$V_{RWM} = 24V$			0.5
Clamping voltage <sup>1)</sup>	$V_{CL}$	V	$I_{PP} = 1A, t_p = 8/20\mu s$			30
		V	$I_{PP} = 200A, t_p = 8/20\mu s$			32
Junction capacitance	$C_J$	pF	$V_R = 0V, f = 1MHz$			800

Notes:

(1). Non-repetitive current pulse, according to IEC61000-4-5.

## ■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
PESD24VP4A1	F1	Approximate 010	3000	30000	120000	7" reel



# PESD24VP4A1

## ■ Characteristics (Typical)

Fig.1 8/20 $\mu$ s waveform per IEC61000-4-5




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Clamping voltage vs. Peak pulse current




Fig.4 Capacitance vs. Reverse voltage




Fig.5 Non-repetitive peak pulse power vs. Pulse time






Fig.6 Power derating vs. Ambient temperature






# PESD24VP4A1

## ■ Outline Dimensions



SYM	MILLIMETERS		
	MIN	NOM	MAX
A	0.45	0.50	0.60
A1	0.15REF		
A2	0.00	0.02	0.05
b	0.25	0.30	0.35
b1	0.22REF		
D	1.95	2.00	2.05
D1	1.45	1.50	1.55
E	1.95	2.00	2.05
E1	1.00	1.05	1.10
e	1.30BSC		
L	0.35	0.40	0.45
L1	0.20	0.25	0.30

## ■ Recommended PCB Layout



Unit: mm

### Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.